

# BETCO® MATTE FINISH



## Low gloss floor finish

This floor finish was specifically designed for facilities which require a protective coating on floors but prefer a low gloss appearance. It is a durable, low maintenance finish which is easy to apply and maintain. The low gloss appearance makes this finish perfect for use in healthcare facilities.

## Features

- Low gloss
- Self-sealing
- Extended wear formula
- 0.0% Free Styrene

## Available In

**4 - 1 Gal. Bottles Item #66504-00**

## Directions for Use

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

**RESTORATIVE MAINTENANCE:** Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on Betco stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 3 coats of finish is recommended. Note: This product is a self-sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a Betco sealer will extend the long term performance.

**ROUTINE MAINTENANCE:** Sweep large debris and dust mop. Damp mop or automatic scrub using a Betco floor cleaner.

**INTERIM MAINTENANCE:** Sweep large debris and dust mop. Top scrub the floor using Daily Scrub SC and maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above.

Please recycle empty containers. Note: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

## Tech Specs

Color (dried)	Crystal clear
Color (liquid)	White
Coverage	2000 - 3000 square feet/gallon
Drying time	30 - 40 minutes
Fragrance	Mild
Gloss (ASTM D 1455-87)	1 coat 30 -35 2 coats 35 - 40
Heel mark resistance	Very good
Leveling	Excellent
pH	7.0 - 8.5
Powdering resistance	Excellent
Recoat	Very good
Shelf life	1 year
Specific gravity	1.06