

MATERIAL SAFETY DATA SHEET

	1. Product and Company Identification
Product number	848-003
Product name	Industrial Plastic Cleaner
Effective date	20-Feb-2011
Company information	Sprayway, Inc. 1005 Westgate Addison, IL 60101 United States
Company phone	General Assistance 630-543-7600
Emergency telephone US	800-424-9300
Emergency telephone outside US	703-527-3887
Version #	09
Supersedes date	14-Oct-2009
	2. Hazards Identification
Emergency overview	CONTENTS UNDER PRESSURE. Aerosol. Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Prolonged exposure may cause chronic effects.
Potential health effects	
Routes of exposure	Ingestion. Skin contact. Eye contact.
Eyes	Contact may irritate or burn eyes. Eye contact may result in corneal injury.
Skin	This product may be harmful if it is absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.
Ingestion	Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.
Target organs	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans. Central nervous system. Lungs.
Chronic effects	Unconsciousness. Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.
Signs and symptoms	Discomfort in the chest. Corneal damage. Narcosis. Cyanosis. Conjunctivitis. Defatting of the skin. Irritation.
3	. Composition / Information on Ingredients

Components	CAS #	Percent
2-Butoxyethanol	111-76-2	3 - 5
Ethyl Alcohol	64-17-5	3 - 5
Propane	74-98-6	1 - 3
n-Butane	106-97-8	1 - 3
Non-hazardous and other components below reportable levels		80 - 90

4. First Aid Measures

First aid procedures

Eye contact

Skin contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Product name: Plastic Cleaner Product #: 848 Industrial Plastic Cleaner

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Ingestion	If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Notes to physician	Symptoms may be delayed.
	5. Fire Fighting Measures
Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media Protection of firefighters	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
	6. Accidental Release Measures
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.
	7. Handling and Storage
Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 1 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep the container dry. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 1 Aerosol (NFPA 30B) Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.
	8. Exposure Controls / Personal Protection

CAS #	TWA	OTEL	a
		STEL	Ceiling
111-76-2	20 ppm	Not established	Not established
64-17-5	1000 ppm	1000 ppm	Not established
74-98-6	1000 ppm	Not established	Not established
106-97-8	1000 ppm	Not established	Not established
	111-76-2 64-17-5 74-98-6	111-76-2 20 ppm 64-17-5 1000 ppm 74-98-6 1000 ppm	111-76-2 20 ppm Not established 64-17-5 1000 ppm 1000 ppm 74-98-6 1000 ppm Not established

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

i electiai protocarte equipinent	
Eye / face protection	Wear chemical goggles.
Skin protection	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	204.8 °F (96.1 °C) estimated
Color	Pale yellow
Density	0.9583 g/cm3 estimated
Flammability (HOC)	4.0975 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Liquid. Aerosol.
Freezing point	Not available
Odor	Butyl
рН	9.5 - 10.5
Physical state	Liquid.
Pressure	90 - 110 psig @ 70F
Solubility	Partially
Specific gravity	0.9584 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hannahara da sana sakésa ana dasta	

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LD50: 5684 mg/kg estimated, Rat, Dermal			
Component analysis - LD50				
Toxicology Data - Selected	LD50s and LC50s			
2-Butoxyethanol	111-76-2	Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg		
Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h		
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h		
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h		
Sensitization	Not expected to be hazardous by OSHA criteria.			
Carcinogenicity				
IARC - Group 1 (Carcinoge	nic to Humans)			
Ethyl Alcohol	64-17-5	Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in preparation] (in alcoholic beverages)		
Teratogenicity	Not exp	ected to be hazardous by OSHA criteria.		

	12. Ecological Information
Ecotoxicity	Components of this product have been identified as having potential environmental concerns.
	LC50 28864 mg/L, Fish, 96.00 Hours,
	EC50 22852 mg/L, Daphnia, 48.00 Hours,
	IC50 11968 mg/L, Algae, 72.00 Hours,
	13. Disposal Considerations
Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this materiat to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.
	14. Transport Information
Department of Transportation (DOT)	Requirements
Basic shipping requirements:	
Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None
IMDG	
Basic shipping requirements:	
Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F 2
Labels required	None
Transport Category	2
IATA	
Basic shipping requirements:	
Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1

US federal regulations		ct is a "Hazardous Chemical" as defined by the OSHA Hazard Communication 29 CFR 1910.1200.
U.S CERCLA/SARA - Section 31	3 - Emission Re	eporting
2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)

Product name: Plastic Cleaner

Product #: 848 Industrial Plastic Cleaner

	Administration						
29 CFR 1910.1200 hazardous chemical	s Yes						
CERCLA (Superfund) reportable	quantity						
None							
Superfund Amendments and Re	authorization /	Act of 1986 (SARA)					
Section 302 extremely hazardous substance	No						
Section 311 hazardous chen	nical Yes						
Hazard categories (311/312)	Delayed Fire Haza Pressure	te Hazard - Yes Hazard - Yes ard - Yes Hazard - Yes y Hazard - No					
Inventory status							
Country(s) or region	Inventory na	me	On inventory (yes/no)*				
China	-	Existing Chemical Substances in China (IECSC)	No				
Europe		entory of New and Existing Chemicals (EINECS)	Yes				
Europe	European List	t of Notified Chemical Substances (ELINCS)	No				
Japan	Inventory of E	Inventory of Existing and New Chemical Substances (ENCS)					
Korea	-	nicals List (ECL)	No				
United States & Puerto Rico	-	nces Control Act (TSCA) Inventory	Yes				
A "Yes" indicates that all compone		ct comply with the inventory requirements administered b	by the governing country(s)				
State regulations							
U.S Pennsylvania - RTK (Righ	nt to Know) List						
2-Butoxyethanol	, 111-76-2	Present					
Ethyl Alcohol	64-17-5	Present					
n-Butane Propane	106-97-8 74-98-6	Present Present					
	14 00 0						
		16. Other Information					
Further information	HMIS® is	s a registered trade and service mark of the NPCA.					
	Health: 1						
HMIS [®] ratings							
HMIS® ratings	Flammab						
-	Physical	hazard: 0					
HMIS® ratings Disclaimer	Physical The inform knowledg designed disposal information material u in the tex	hazard: 0 mation provided in this Safety Data Sheet is correc ge, information and belief at the date of its publication only as a guidance for safe handling, use, process and release and is not to be considered a warranty on relates only to the specific material designated a used in combination with any other materials or in a st.	on. The information given is sing, storage, transportation, or quality specification. The and may not be valid for such				
-	Physical The inform knowledg designed disposal a information material u in the tex Product a Compositi Hazards Hazards Hazards Physical	hazard: 0 mation provided in this Safety Data Sheet is correc ge, information and belief at the date of its publication only as a guidance for safe handling, use, process and release and is not to be considered a warranty on relates only to the specific material designated a used in combination with any other materials or in a	on. The information given is sing, storage, transportation, or quality specification. The and may not be valid for such any process, unless specified				